



43145 - Vehicle Wiring Installation Instructions

Honda CR-V 2007 - 2011

1. Open the rear hatch and remove storage area cover, rubber mat & spare tire cover.
2. Remove the driver and passenger side D-rings and remove the trunk scuff fascia panel.
3. Carefully pull back the driver side interior trim panel. Start separating the trim panel in the rear of the vehicle and work your way up and forward to expose the vehicle's white trailer tow plug.
4. Attach the Hopkins® T-Connector from the converter module with the matching connector. Attach connector's being careful not to damage the connector locking tabs.
5. On the drivers side locate and secure the T-Connector black converter module with ny-ties (provided) to prevent damage or rattling and being careful to avoid areas that would cut or pinch the wire.
6. Route the 4-wire flat connector to near the center of the rear hatch opening. The 4-way flat connector can now be laid on the flat surface to the right or left of the rear hatch latching mechanism so that it will let the 4-wire flat hang out undamaged from under the rear hatch lid when closed for towing. Stow 4-flat connector in the spare tire area when not in use.
7. Reinstall the threshold, trim panel, rubber mat, cargo net and spare tire cover.
8. Attach the 4-way flat dust cover (provided) to the 4-way flat connector.
9. Apply a small amount of grease (provided) to the 4-way flat terminals to prevent corrosion.
10. Plug completed wire harness into the trailer 4-way flat connector.
11. Test all functions with the engine running to ensure proper operation.
12. Caution: Overloading circuit can cause fires. Don't exceed lower of towing manufacturer rating or :
Max. stop/turn light: 1 lamp per side (3 amps)
Max. tail lights: (6 amps)
Read vehicle's owners manual & instruction sheet for additional information.

NOTE: Hopkins® T-Connector fuse holder assembly requires an ATM 15 amp. Mini-Fuse replacement if blown.

TIPS:

Grease applied to the wiring terminals on a regular basis will help prevent corrosion.

Always unplug boat trailer connector before backing trailer into the water.

Need Help? (English Only)
1-800-835-0129
techsupport@hopkinsmfg.com
www.hopkinstowingsolutions.com