



INSTALLATION INSTRUCTIONS FOR PART 99-7404

APPLICATIONS NISSAN Maxima 2004-2006

99-7404



KIT FEATURES

ISO DIN Head unit provision
with pocket

KIT COMPONENTS

A) Radio Housing Panel • B) (4) Panel retaining Clips



A



B

TOOLS REQUIRED:

Phillips Screwdriver • Small Flat Blade Screwdriver



1-800-221-0932



www.metraonline.com

© COPYRIGHT 2004-2007 METRA ELECTRONICS CORPORATION



99-7404

TABLE OF CONTENTS

NISSAN MAXIMA

***Dash Disassembly*1-2**

***ISO DIN Head Unit Provision*3**

***Final Assembly*4**

***Notes*5**



99-7404

2004-2006 NISSAN MAXIMA

DASH DISASSEMBLY

- 1** Disconnect the negative battery terminal to prevent an accidental short circuit.

A



- 2** Twist and slide down the cover at the base of the shift knob. **(Figure A)**

B



- 3** Remove the retaining clip at base of shift knob and pull up to remove. **(Figure B)**

C



- 4** Unclip and remove panel surrounding shift knob. **(Figure C)**

E



- 5** Remove (2) Phillips screws at the bottom of the radio panel and unclip and remove. **(Figure E)**



99-7404

DASH DISASSEMBLY

6 Remove (2) Phillips screws at the bottom of the display panel and unclip and remove the panel. **(Figure F)**

F



7 Remove (4) Phillips screws to remove the audio/climate control/display as one unit. **(Figure G)**

G



8 Remove (4) Phillips screws from each side of radio/tuner to remove from audio/climate control/display bracket assembly.

9 Remove the (4) Phillips screws securing the factory climate control button assembly to the radio panel and remove. Note: Retain all hardware to be used in Kit Assembly. **(Figure H)**

H



10 Remove (4) Phillips screws securing the factory pocket assembly to the radio panel and remove. Note: Retain all hardware to be used in Kit Assembly. **(Figure I)**

I





99-7404

ISO DIN HEAD UNIT PROVISIONS:

- 1** Position the aftermarket radio into audio/climate control/display bracket assembly and secure using the bottom (2) Phillips screw positions and the factory hardware. **(Figure A)**




- 2** Install the (4) supplied retaining clips onto the 99-7404 in the same locations as the factory radio panel. **(Figure B)**



- 3** Using the factory hardware secure the factory climate control button assembly into the 99-7404. **(Figure C)**



- 4** Using the factory hardware secure the factory pocket assembly into the 99-7404. **(Figure D)**




KIT ASSEMBLY



99-7404

FINAL ASSEMBLY



- A) *Strip wire ends back 1/2"***
- B) *Twist ends together***
- C) *Solder***
- D) *Tape***

- 1** Locate the factory wiring harness in the dash. Metra recommends using the proper mating adapter and making the connections as shown. (Isolate and individually tape off the ends of any unused wires to prevent electrical short circuit)

- 2** Re-connect the negative battery terminal and test the unit for proper operation.

- 3** Reassemble in reverse order of disassembly using the 99-7404 instead of the factory radio panel.



99-7404

NOTES

A series of horizontal lines spanning the width of the page, intended for handwritten notes. The lines are evenly spaced and extend from the left margin to the right margin, where they terminate at the vertical line of the 'NOTES' label.

INST997404



1-800-221-0932



www.metraonline.com

Rev. 06-15-07 © COPYRIGHT 2004-2007 METRA ELECTRONICS CORPORATION INST99-7404