

K&N Filtercharger® P/N 33-2235

This filter fits: See catalog for current listings

FREE K&N DECAL** To register your warranty, please see us online at knfilters.com/register. **FREE K&N DECAL Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modifications will be required. However the following procedure **MUST** be followed to ensure a proper fit and seal of the K&N Filtercharger®.

- 1) Loosen the hose clamp on the intake hose at the airbox and remove the hose from the airbox.
- 2) If vehicle is equipped with an air temp. sensor, see figure 2, if not, proceed to step 4. .
- 3) Remove the air temperature sensor connector from the sensor.
- 4) Unfasten the screws and or clips.
- 5) Remove the airbox lid from the vehicle.
- 6) Remove the old filter.
- 7) Wipe any dirt out of the lid or base. The airbox lid must be clean and dry so that the gaskets will stick to it.
- 8) Apply the self-adhering gasket. (See fig. 1)
- 9) Install the K&N air filter into the airbox base.
- 10) Re-assemble in reverse order.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2