



Installation Instructions BM1TS Universal Tire Strap

Universal Tire Strap Installation Instructions

Hardware Kit Contains:

- (6) 5/16" x 1" Washers
- (6) 5/16" x 1" Pan Head Hex Screws

Recommended Tools:

- Allen Wrench Set
- Marker
- Drill and 1/2" Drill Bit

PLEASE READ EACH STEP COMPLETELY BEFORE INSTALLATION

Step 1: Place your spare tire in your desired mounting position. Make sure it is centered from side to side.

Step 2: Place the one upper mounting bracket with the rectangular hole in it at the 12 o'clock position under the tire. Make sure that the screw holes are covered completely by the tire.

Step 3: Place the other two upper mounting brackets with the elongated kidney shaped holes at approximately the 4:30 and 7:30 positions. Make sure the screw holes are covered completely by the tire.

Step 3: Carefully remove your spare tire without moving the brackets. Once removed pay attention to where the brackets are located and look under the bed of the truck to make sure that once you drill holes that you will not hit any gas lines, brake lines, frame sections or any other wiring, etc. Also, make sure that once they are drilled that you will be able to slide the under bed mounts into position. If this cannot be done then you will need to mount your spare tire in a different place.

Step 4: Once the upper mounts are placed correctly you can now mark and drill the holes. Once drilled make sure you have access to all bolt holes and you can mount the brackets using the supplied Pan Head Screws and Washers. Remember that there is some side-to-side adjustment on the brackets to get them into the correct positions.

Step 5: Get the strap that is loose from the rest and snap it into the mounting bracket.

Step 6: Place your spare tire into position over the brackets and use the remaining straps and the already used strap to tighten down.



Products licensed to N-FAB Inc., by Fichter Designs, are protected by US Patent Law and International Copy Right Law. US Patent #6588783, # 6874801, #7416202 apply. Other patents and continuances are pending. Fichter Designs products configurations are also protected by International Trade Dress Law. All Design and Patent infringements will be prosecuted to the full extent of the law.

For Technical Support / Assistance Please Call 866-806-NFAB(6322)

N-FAB Inc. - 12302 Shiloh Church Rd., Houston, TX 77066